



FRONT LIGHT

INSERT BATTERIES

1. To insert batteries, remove the rear cover by turning counter-clockwise. (Fig.1)
2. Remove the battery case then insert 2 CR2032 batteries according to the polarity markings on the case. (Fig.2)




(Fig.1)



CR2032 x 2
(Fig.2)


INSTALLATION

1. Pull the strap to fix into the bulge first.
2. Install the light onto the handlebar and tighten it by strap.



TO SWITCH MODES

Press the lens on the front of the light.



SPECIFICATIONS

Size:	40 × 28 × 33 mm
Weight:	31 g
LED:	Front light: 1 SMD White LED Rear light: 1 SMD Red LED
Battery:	CR2032 x 2
Bracket:	Front light: Ø19-Ø32, with 2 rubber pads Rear light: Ø19-Ø32, with 1 rubber pad




REAR LIGHT

INSERT BATTERIES

- 1.To insert batteries, remove the rear cover by turning counter-clockwise.(Fig.1)
- 2.Remove the battery case then insert 2 CR2032 batteries according to the polarity markings on the case.(Fig.2)




(Fig.1)



CR2032 x 2
(Fig.2)


INSTALLATION

1. Pull the strap to fix into the bulge first.
2. Install the light onto the seat post or seat stay and tighten it by strap.



TO SWITCH MODES

Press the lens on the front of the light.



⚠ Caution:

- 1.We recommend to remove batteries from the light during period of non-use to avoid the battery leakage.
- 2.For best performance, do not mix new and old batteries.
- 3.Carefully install batteries, insuring proper polarity.
- 4.For your own safety, please do not operate the controls of the product while riding.
- 5.Please keep the product out of children's reach.