

FOR BIKE

MOUNTING YOUR BRACKET

Install the light on the handlbar, seat post or seat stay by using strap or cable tie.

(Front Light) (Rear Light)









Tighten up the cable tie and cut the extra part of it by using scissors.

MOUNTING YOUR LIGHT

When the light and bracket is in horizontal condition, install the light on the bracket and twist it in the position of 90° and fasten it.

(Front Light)









LIGHT REMOVAL

Twist the light in the direction of right or left into 90° and remove it from bracket. (Front Light) (Rear Light)







FOR CAMPING

MOUNTING YOUR LIGHT

Twist the light in the direction of right or left into 45° and fasten it.





ADJUST YOUR HEAD STRAP

1.slide the plastic adjuster forward or backward to loosen or tighten the head strap.

2. 90 degree rotatable angle





BATTERY INSTALLATION

- 1.Remove the lens by placing a coin in the side slot and twist untill the two sides separate.
- 2.Install 2 new CR2032 battery into the battery connector one by one, then put the case back





REMIND

Please remove battery insulation sheet before first use



COMPONENTS

Light / brackets / straps / pads / cable tie x 2 / head strap













TO SWITCH MODES

Press the button on the front of the light.















SPECIFICATIONS

Size: 30 X 30 X 21 mm Weight: 25g (without battery) LED: 1 White LED and 2 Red LEDs

Battery: CR2032 x 2 Accessories: Head strap

PRODUCT WARRANTY

INFINI offers a Two-year Limited Warranty from the date of original purchase. Products are warranted to be free from manufacturing defects in materials and workmanship under normal

use.

Batteries are covered by 90 days warranty(only for rechargeable light), To obtain warranty service, products should be returned with proof of purchase from an authorized retailer.

